

Part No. 809430A

# SIBERIA XPA DR LED BAR 50"



## SIBERIA XPA DR LED BAR 50"

WHITE / AMBER POS. | HELLO FUNC. | 2,5M CABLE  
The Siberia XPA Double Row 50" LED bar has a maxed-out illumination with 30000 actual lumens and a more than 1250-meter range in Xperience mode.

[Read more](#)



|                               |                                                                         |                          |                    |
|-------------------------------|-------------------------------------------------------------------------|--------------------------|--------------------|
| Voltage (DC)                  | 10-32 V DC                                                              | Material housing/chassi  | Aluminium          |
| Consumption                   | 410 W                                                                   | Material lens            | Polycarbonate      |
| Functions                     | Amber Pos., White pos., Xperience mode, E-approved mode, Hello function | Length                   | 1279.4 mm          |
| Consumption specific function | Amber pos. 18W, E-mode 19W, X-mode 410W, White pos. 18.5W               | Depth                    | 71.6 mm            |
| Actual lumen                  | 30000 lm                                                                | Height                   | 76 mm              |
| 1 lux @                       | 1258 m                                                                  | Height including bracket | 96.6 mm            |
| Color temperature             | 5700 K                                                                  | IP-class                 | IP68/69K           |
| Beam pattern                  | Long-distance beam                                                      | Operating temperature    | -35 - +60 °C       |
| Connection                    | Cable                                                                   | E-approved               | Yes                |
| Cable length                  | 2500 mm                                                                 | ECE approval             | R10.06, R148, R149 |

